

**TECHNICAL  
INFORMATION**



# Rainbow Membrane



## PRODUCT

Rainbow Membrane is a pre mixed, ready to use straight from the pail, water based acrylic protective coating. Rainbow membrane can easily be tinted to almost any colour from the most popular of colour ranges available. Rainbow membrane will enhance, protect and promote easy cleaning of any rendered or textured substrate.

## SURFACE & PRODUCT PREPARATION

It is imperative that the substrate Rainbow Membrane is to be applied to is totally clean and removed of all loose paint, dirt, dust, grease, etc. Failure to do so can cause delamination resulting in damage to the finish product.

Insulcon takes no responsibility for problems arising from this.

Although Rainbow Membrane is a pre mixed ready to use product, Insulcon recommends that the drum is agitated before use. This will make sure no separation of ingredients or colour tints has occurred, therefore meaning the product is of its highest standard.

## COVERAGE

Rainbow Membrane when used according to manufacturers directions will cover approx 40 square metres on a first coat application, and approx 60 square metres on a 2nd coat application. These may vary depending on substrate type and applicator ability.



Insulcon Pty Ltd  
34 Swift Way  
Dandenong South  
VIC, 3175

Ph : 9768 2335  
Fax: 9768 2337  
E-mail: [sales@insulcon.com.au](mailto:sales@insulcon.com.au)  
Web : [insulcon.com.au](http://insulcon.com.au)

**TECHNICAL  
INFORMATION**



# Rainbow Membrane



## APPLICATION

Rainbow Membrane is best applied using a roller. For maximum results in finish and protection, Rainbow Membrane should be applied in 2 coats. The 1st coat should have full coverage of the entire substrate. This will partially seal the surface of the substrate which will aid the application of the 2nd coat. The 2nd coat will be the resultant product, so extra care must be taken in this application.

Applicator should be familiar with the correct application process of Rainbow Membrane as Insulcon will take no responsibility for poor workmanship.

Rainbow Membrane should only be applied in suitable weather. Rain, frost, excessive cold/warmth and windy conditions are not suitable conditions for Rainbow Membrane application. The applicator should be familiar with these common sense limitations.

NOTE –All exterior coatings will fade overtime. Dark colours have a tendency to fade quicker. Some dark colours due to excessive tinting saturation, are unable to be made.

\*Contact Insulcon for more information on colour tinting

## SAFETY

If swallowed: Rinse mouth and lips with water. Seek medical advice if discomfort occurs.

If in Eyes: Flush eyes thoroughly with flowing water for 15 minutes.

Seek medical attention symptoms persist.

If on skin: Wash thoroughly with soap and water.

If Inhaled: Remove subject to fresh air. If symptoms persist seek medical attention.



Insulcon Pty Ltd  
34 Swift Way  
Dandenong South  
VIC, 3175

Ph : 9768 2335  
Fax: 9768 2337  
E-mail: [sales@insulcon.com.au](mailto:sales@insulcon.com.au)  
Web : [insulcon.com.au](http://insulcon.com.au)