

**TECHNICAL
INFORMATION**



Rainbow Prime



Insulcon Pty Ltd
34 Swift Way
Dandenong South
VIC, 3175

Ph : 9768 2335
Fax: 9768 2337
E-mail: sales@insulcon.com.au
Web : insulcon.com.au

PRODUCT

Rainbow Prime is a pre mixed, ready to use straight from the pail, water based acrylic protective sealer. Rainbow Prime can easily be tinted to almost any colour from the most popular of colour ranges available. Rainbow Prime is ideal for priming a rendered substrate in preparation for application of Rainbow Texture.

SURFACE

&

PRODUCT PREPARATION

It is imperative that the substrate Rainbow Prime is to be applied to is totally clean and removed of all loose paint, dirt, dust, grease, etc. Failure to do so can cause delamination resulting in damage to the finish product.

Insulcon takes no responsibility for problems arising from this.

Although Rainbow Prime is a pre mixed ready to use product, Insulcon recommends that the drum is agitated before use. This will make sure no separation of ingredients or colour tints has occurred, therefore meaning the product is of its highest standard.

COVERAGE

Rainbow Prime when used according to manufacturers directions will cover approx 65-75 square metres on an application. Rainbow Prime is best used when the substrate is coated once with Prime then a coat of Rainbow Texture/Membrane.

**TECHNICAL
INFORMATION**



Rainbow Prime



APPLICATION

Rainbow Prime is best applied using a roller. For maximum results in finish and protection, Rainbow Prime should be applied in 1 coat to the entire substrate. This will prime the surface of the substrate which will aid the application of Rainbow Texture/Membrane.

Applicator should be familiar with the correct application process of Rainbow Prime as Insulcon will take no responsibility for poor workmanship.

Rainbow Prime should only be applied in suitable weather. Rain, frost, excessive cold/warmth and windy conditions are not suitable conditions for Rainbow Prime application. The applicator should be familiar with these common sense limitations.

NOTE –All exterior coatings will fade overtime. Dark colours have a tendency to fade quicker. Some dark colours due to excessive tinting saturation, are unable to be made.

*Contact Insulcon for more information on colour tinting

SAFETY

If swallowed: Rinse mouth and lips with water. Seek medical advice if discomfort occurs.

If in Eyes: Flush eyes thoroughly with flowing water for 15 minutes.

Seek medical attention symptoms persist.

If on skin: Wash thoroughly with soap and water.

If Inhaled: Remove subject to fresh air. If symptoms persist seek medical attention.



Insulcon Pty Ltd
34 Swift Way
Dandenong South
VIC, 3175

Ph : 9768 2335
Fax: 9768 2337
E-mail: sales@insulcon.com.au
Web : insulcon.com.au